

List No. EPX304/USB/DGL

13A 1 Gang Switched Socket with USB Outlet (Total 2.1A) Gold Finish

- Crabitree
- Smooth and slimline profile
- Clip on front plate for clean screwless aesthetic
- 5V USB Output
- 2.1A USB Output
- Gold Finish

Product Specification Data	Revision Date: 15/10/2021
Product Standard/s	BS 1363-2
Terminal Capacity L&N	3 x 1.5, 3 x 2.5, 2 x 4.0 mm ²
Terminal Capacity E	3 x 1.5, 3 x 2.5, 2 x 4.0 mm ²
CE Conformity	Yes
WEEE Symbol	Yes
G Mark	Yes
UKCA Conformity	Yes
Operating voltage	250 V
Frequency	50 Hz
Max. output current	2100 mA
Output voltage	5 V
Mounting method	Surface mounted (plaster)
Colour	Gold
Min. depth of built-in installation box	35 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE 01543 455000 www.electrium.co.uk info@electrium.co.uk