



- Made from tough & durable thermoplastic
- Ingress Protection rating IP66
- Ready made knockouts for cable entry
- Optimal space for wiring
- Robust enclosure

Product Specification Data

Revision Date: 23/04/2024

| | |
|--|--|
| Product Standard/s | BS EN 60669-1 |
| Terminal Capacity L&N | 4 x 1.0, 3 x 1.5, 1 x 2.5 mm ² |
| Terminal Capacity E | 11 x 1.0, 3 x 1.5, 1 x 2.5 mm ² |
| Frequency | 50 Hz |
| CE Conformity | Yes |
| WEEE Symbol | Yes |
| UKCA Conformity | Yes |
| Wiring system | Two-way switch |
| Method of operation | Rocker/button |
| Assembly arrangement | Basic element with complete housing |
| Number of modules (module system) | 0 |
| Push button switch | Yes |
| Number of rockers | 1 |
| Mounting method | Surface mounted |
| Type of fastening | Screw mounting |
| With mounting plate | Yes |
| Material | Plastic |
| Material quality | Thermoplastic |
| Halogen free | Yes |
| Surface protection | Other |
| Surface finishing | Glossy |
| Colour | Grey |
| Illumination | Optional |
| Function lighting | Other |
| Suitable for degree of protection (IP) | IP66 |
| Nominal voltage | 250 V |
| Rated current | 20 A |
| Connection type | Screwed terminal |
| Device width | 96 mm |

| | |
|---------------|---------|
| Device height | 96 mm |
| Device depth | 86.3 mm |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk