



- Made from tough & durable thermoplastic
- Ingress Protection rating IP66
- Ready made knockouts for cable entry
- Optimal space for wiring
- Robust enclosure

Product Specification Data		Revision Date: 23/04/2024
Product Standard/s	BS EN 60669-1	
Terminal Capacity L&N	4 x 1.0, 3 x 1.5, 1 x 2.5 mm ²	
Terminal Capacity E	7 x 1.0, 3 x 1.5, 1 x 2.5 mm ²	
Frequency	50 Hz	
CE Conformity	Yes	
WEEE Symbol	Yes	
UKCA Conformity	Yes	
Wiring system	Two-way switch	
Method of operation	Rocker/button	
Assembly arrangement	Basic element with complete housing	
Number of modules (module system)	0	
Push button switch	Yes	
Number of rockers	1	
Mounting method	Surface mounted	
Type of fastening	Screw mounting	
With mounting plate	Yes	
Material	Plastic	
Material quality	Thermoplastic	
Halogen free	Yes	
Surface protection	Other	
Surface finishing	Glossy	
Colour	Grey	
Illumination	Optional	
Function lighting	Other	
Type of lighting	Incandescent lamp	
Suitable for degree of protection (IP)	IP66	
Nominal voltage	250 V	
Rated current	20 A	
Switching current for fluorescent lamps	20 AX	

Connection type	Screwed terminal
Device width	96 mm
Device height	96 mm
Device depth	86.3 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk