



List No. FALNMRS9SLMA

NH / NM / NMX

9 Way Split Load Meter Cabinet Consumer Unit 100A Main Switch, 80A 30mA RCD, Flexible Configuration



- All metal meter cabinet consumer unit
- Flexible busbar assembly
- 9W Split load
- 320mm fixing centres
- 1x 80A 30mA type A RCCB

Product Specification Data

Revision Date: 15/10/2021

Mounting method	Other
Number of phases	1
Protection	Miniature- / earth leakage circuit breaker
Total number of groups	2
Number of poles main switch	2
Main switch rated current	100 A
Over voltage protection	No
Material housing	Steel
Degree of protection (IP)	IP2XC
Height	257 mm
Width	335 mm
Width in number of modular spacings	13
Depth	119 mm
Extension possible	No
With transparent cover	No
Lockable	No
Product Standard/s	BS EN 61439-3
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Amperage	100 A
Operating Voltage	230 V
Type of Current	AC
Consumer Unit Type	Split load
Total final circuit modular ways	9
Busbar type	Flexible
Main switch rating	100 A
Main switch final circuit modular ways	Flexible

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electricum website.

RCD 1	80A 30mA type A
RCD 1 final circuit modular ways	Flexible
Bespoke application	Meter cabinet
Colour RAL	9010

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk