



- Made from tough & durable thermoplastic
- Ingress Protection rating IP66
- Ready made knockouts for cable entry
- Optimal space for wiring
- Robust enclosure

### Product Specification Data

Revision Date: 23/04/2024

Product Standard/s	BS EN 60669-1
Terminal Capacity L&N	4 x 1.0, 3 x 1.5, 1 x 2.5 mm <sup>2</sup>
Terminal Capacity E	12 x 1.0, 3 x 1.5, 1 x 2.5 mm <sup>2</sup>
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Wiring system	2-pole switch
Method of operation	Rocker/button
Assembly arrangement	Basic element with complete housing
Number of modules (module system)	0
Push button switch	Yes
Number of rockers	1
Mounting method	Surface mounted
Type of fastening	Screw mounting
With mounting plate	Yes
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Surface protection	Other
Surface finishing	Glossy
Colour	Grey
Illumination	Optional
Function lighting	Other
Suitable for degree of protection (IP)	IP66
Nominal voltage	250 V
Rated current	20 A
Connection type	Screwed terminal
Device width	96 mm

Device height	96 mm
Device depth	86.3 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



**Electrium Sales Limited**, Walkmill Lane, Cannock WS11 0XE  
01543 455000 [www.electrium.co.uk](http://www.electrium.co.uk) [info@electrium.co.uk](mailto:info@electrium.co.uk)