



## List No. MESB-20NO

20A Contactor 2 Pole 1 Module (Normally Open)



- Two pole 20A contactor
- Two normally open poles
- Single module DIN rail mounting
- Switch position indication
- Maximum terminal capacity; coil 2.5mm<sup>2</sup>, main poles 10mm<sup>2</sup>

Product Specification Data		Revision Date: 15/10/2021
Rated operating voltage	400 V	
Rated operation current	20 A	
Rated excitation voltage	230 V	
Voltage type (operating voltage)	AC	
Voltage type (excitation voltage)	AC	
Number of contacts as normally open contact	2	
Number of contacts as normally closed contact	0	
Slider for hand switch	No	
Number of modular spacings	1	
Built-in depth	60 mm	
Additional equipment possible	No	
Degree of protection (IP)	IP20	
Product Standard/s	IEC/EN 61095, IEC/EN 60947-4-1, IEC/EN 60947-5-1	
Frequency	50 Hz	
CE Conformity	Yes	
WEEE Symbol	Yes	
UKCA Conformity	Yes	
Height	85 mm	
Width	17 mm	
Depth	65 mm	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.