

List No. NHESPDKIT1

NH DISTRIBUTION

Wylex enclosed SPD kit Type 1 with 10kA MCB



- Accessory for NH Distribution Boards
- Supplied with Type 1 SPD, 10kA MCB (for SPD protection), cable loom kit & enclosure for mounting to the side of the distribution board
- Can be mounted on either the left hand side or the right hand side of the distribution board
- Nominal Voltage (AC) 240/415

Product Specification Data	Revision Date: 21/06/2024
System configuration DC	No
System configuration IT	No
System configuration TN	No
System configuration TN-C	No
System configuration TN-C-S	Yes
System configuration TN-S	Yes
System configuration TT	Yes
System configuration other	No
Number of conductors (without earthing)	4
Nominal discharge surge current (8/20)	25 kA
Max. continuous voltage AC	350 V
Max. discharge surge current (8/20)	100 kA
Mounting method	Surface mounted
Voltage protection level	1.5 kV
Max. conductor cross section solid (solid, stranded)	35 mm²
Max. conductor cross section flexible (fine-strand)	25 mm²
With remote signalling contact	Yes
Signalling at the device	Optical
Category type 2	No
Product Standard/s	BS EN 61643-11
Terminal Capacity L&N	25 mm²
Terminal Capacity E	25 mm²
Frequency	50/60 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Colour RAL	7035
Height	212 mm
Width	180 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Product Specification Data (cont)	Revision Date: 21/06/2024
i roddol opcollodion Dala (cont)	1 (0 / 10 / 10 / 10 / 10 / 10 / 10 / 10

Depth 124 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

