



List No. NHLPV0412S

NH DISTRIBUTION

Vertical Lighting & Power 4 + 12-Way STD



NHLPV0404S
SHOWN

- Part L2 compliant
- Switch disconnecter incoming device included
- Individual isolation of each section and total board
- Fully rated 125A lighting (top) board
- Separate lighting and power meter readings through one dual channel meter

Product Specification Data

Revision Date: 14/06/2022

Mounting method	Surface mounted (plaster)
Number of phases	3
Number of poles main switch	3
Main switch rated current	125 A
Material housing	Steel
Degree of protection (IP)	IP31
Height	1548 mm
Width	430 mm
Depth	155 mm
Extension possible	Yes
Lockable	Yes
Product Standard/s	BS EN 61439-3
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Amperage	125 A
Fault Rating	12
Pole Configuration	TPN
Operating Voltage	415 V
Type of Current	AC
Busbar type	FIXED SOLID COPPER
Colour RAL	7035

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk