



List No. NHLPV0604M

NH DISTRIBUTION

Vertical Lighting & Power 6 + 4-Way MID



NHLPV0404M
SHOWN

- Part L2 compliant with MID certified meters
- Switch disconnecter incoming device included
- Individual isolation of each section and total board
- Fully rated 125A lighting (top) board
- Separate lighting and power meter readings through one dual channel meter

Product Specification Data		Revision Date: 14/06/2022
Mounting method	Surface mounted (plaster)	
Number of phases	3	
Number of poles main switch	3	
Main switch rated current	125 A	
Material housing	Steel	
Degree of protection (IP)	IP31	
Height	1303 mm	
Width	430 mm	
Depth	155 mm	
Extension possible	Yes	
Lockable	Yes	
Product Standard/s	BS EN 61439-3	
Frequency	50 Hz	
CE Conformity	Yes	
WEEE Symbol	Yes	
UKCA Conformity	Yes	
Amperage	125 A	
Fault Rating	12	
Pole Configuration	TPN	
Operating Voltage	415 V	
Type of Current	AC	
Busbar type	FIXED SOLID COPPER	
Colour RAL	7035	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.