



## List No. NHLPV1612ML

### NH DISTRIBUTION

Vertical Lighting & Power 16 + 12-Way MID



- 16W/12W 125A 3P+N Power & Lighting distribution board for commercial applications to aid compliance with Building Regulations Part L2
- Complete with Switch disconnecter and 2 MID certified meters for ease of use by the property manager and installation by the contractor
- Accepts Wylex 10kA and miniature 6kA final circuit protection devices; Single and Triple Pole MCBs from 6A to 63A, Single Pole RCBOs from 6A to 50A and AFDDs from 6A to 40A
- Individual isolation for top and bottom boards which are both fully rated at 125A
- RAL 7035 Grey powder coat finish. Designed and manufactured in the UK to BS EN 61439-3

Product Specification Data		Revision Date: 06/12/2022
Mounting method	Surface mounted (plaster)	
Number of phases	3	
Protection	Miniature- / earth leakage circuit breaker	
Total number of groups	2	
Number of poles main switch	3	
Main switch rated current	125 A	
Material housing	Steel	
Degree of protection (IP)	IP31	
Height	1953 mm	
Width	430 mm	
Depth	155 mm	
Extension possible	Yes	
With transparent cover	No	
Lockable	Yes	
Product Standard/s	BS EN 61439-3	
Frequency	50 Hz	
CE Conformity	Yes	
WEEE Symbol	Yes	
UKCA Conformity	Yes	
Terminal Capacity L&N (Incoming)	50 mm <sup>2</sup>	
Amperage	125 A	
Pole Configuration	TPN	
Operating Voltage	400 V	
Type of Current	AC	
Busbar type	FIXED SOLID COPPER	
Colour RAL	7035	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.