



List No. NHRS204/63

NH / NM / NMX

2 Way Insulated Consumer Unit RCD Incomer 63A 30mA



- Insulated enclosure
- Flexible busbar assembly
- 2W RCD incomer
- 1x 80A 30mA type AC RCCB

Product Specification Data

Revision Date: 15/10/2021

Mounting method	Surface mounted (plaster)
Number of phases	1
Protection	Miniature- / earth leakage circuit breaker
Material housing	Plastic
Degree of protection (IP)	IP2XC
Height	160 mm
Width	117 mm
Width in number of modular spacings	4
Depth	102 mm
Extension possible	No
With transparent cover	Yes
Lockable	No
Product Standard/s	BS EN 61439-3
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Amperage	100 A
Operating Voltage	230 V
Type of Current	AC
Consumer Unit Type	RCD Incomer
Total final circuit modular ways	2
Busbar type	Flexible
Main switch rating	100 A
RCD 1	80A 30mA type AC
RCD 1 final circuit modular ways	Flexible
Colour RAL	7035

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk