



List No. NHSW363X

NH FUSE COMBINATION UNITS

63A 3P+N Enclosed Switch Disconnecter - Size 2



- Enclosed switch disconnecter
- Painted RAL 7035 steel enclosure with hinged door. 325mmH x 157.5mmW x 133.5mmD

Product Specification Data

Revision Date: 15/10/2021

Version as main switch	No
Version as safety switch	No
Max. rated operation voltage Ue AC	415 V
Rated permanent current Iu	63 A
Number of poles	3
Cable entry	Other
Equipped with connectors	Yes
Suitable for ground mounting	No
Suitable for front mounting 4-hole	No
Suitable for busbar mounting	No
Type of control element	Door coupling rotary drive
Position control element	Front side
Motor drive optional	No
Motor drive integrated	No
Version as emergency stop installation	No
Terminal Capacity L&N	25 mm ²
Frequency	50-60 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk