



List No. NHTN20L

NH DISTRIBUTION

20-Way 125A Surface 3P+N Distribution Board



- 20W 3P+N Type 'B' distribution board
- Switch disconnecter, RCCB, or direct connection incomer options available
- Accepts Wylex 10kA and miniature 6kA final circuit protection devices; Single and Triple Pole MCBs from 6A to 63A, Single Pole RCBOs from 6A to 50A and AFDDs from 6A to 40A
- Accepts the Wylex NHCM125INMP (Pulsed Output/Modbus RTU), NHMID125INMP (MID) integral incoming meter kits or NHTNSP125L integral Type 2 surge protection kit
- RAL 7035 Grey powder coat finish. Designed and manufactured in the UK to BS EN 61439-3

Product Specification Data

Revision Date: 07/12/2022

Mounting method	Surface mounted (plaster)
Number of phases	3
Main switch rated current	125 A
Material housing	Steel
Degree of protection (IP)	IP31
Height	1000 mm
Width	430 mm
Depth	155 mm
Extension possible	Yes
With transparent cover	No
Lockable	Yes
Product Standard/s	BS EN 61439-3
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Number of ways (Type 'B' boards)	20
Amperage	125 A
Pole Configuration	TPN
Operating Voltage	400 V
Type of Current	AC
Busbar type	FIXED SOLID COPPER
Colour RAL	7035

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.