



List No. NHTN24L250

NH DISTRIBUTION

24-Way 250A Surface 3P+N Distribution Board



- 24W 250A 3P+N Type 'B' distribution board
- TP or 4P Switch disconnecter, MCCB, or direct connection incomer options available
- Accepts all Wylex 10kA final circuit protection devices; Single Pole and Triple Pole Type B, C, and D MCBs (6A to 80A) and Single Pole Type B and C RCBOs (6A to 50A)
- Accepts the Wylex NHCM250INMP (Pulsed Output/Modbus RTU), NHMID250INMP (MID) integral incoming meter kits or NHTNSP250L integral Type 2 surge protection kit
- RAL 7035 Grey powder coat finish. Designed and manufactured in the UK to BS EN 61439-3

Product Specification Data		Revision Date: 05/12/2022
Mounting method	Surface mounted (plaster)	
Number of phases	3	
Main switch rated current	250 A	
Material housing	Steel	
Degree of protection (IP)	IP31	
Height	1308 mm	
Width	430 mm	
Depth	155 mm	
Extension possible	Yes	
With transparent cover	No	
Lockable	Yes	
Product Standard/s	BS EN 61439-3	
Frequency	50 Hz	
CE Conformity	Yes	
WEEE Symbol	Yes	
UKCA Conformity	Yes	
Number of ways (Type 'B' boards)	24	
Amperage	250 A	
Pole Configuration	TPN	
Operating Voltage	400 V	
Type of Current	AC	
Busbar type	FIXED SOLID COPPER	
Colour RAL	7035	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.