

List No. NHTNSP250

NH DISTRIBUTION BOARDS

250A 10kA Integral Surge Arrester Kit



- Accessory for NH Distribution Boards
- Supplied with Type 2 SPD, 10kA MCB (for SPD protection), cable loom kit & SPD mounting bracket
- 18th edition compliant
- Utilises bottom RH Way for protective MCB
- Nominal Voltage (AC) 240/415

Product Specification Data	Revision Date: 15/10/2021
System configuration DC	No
System configuration IT	No
System configuration TN	No
System configuration TN-C	No
System configuration TN-C-S	No
System configuration TN-S	Yes
System configuration TT	Yes
System configuration other	No
Number of conductors (without earthing)	4
Nominal discharge surge current (8/20)	20 kA
Short-circuit breaking capacity (Isccr)	25 kA
Max. continuous voltage AC	350 V
Max. discharge surge current (8/20)	40 kA
Mounting method	DIN rail (top hat rail) 35 mm
Construction size	4 modular spacing
Max. conductor cross section solid (solid, stranded)	35 mm²
Max. conductor cross section flexible (fine-strand)	25 mm²
Voltage protection level L-N	1.4 kV
Voltage protection level N-PE	1.5 kV
With remote signalling contact	Yes
Integrated backup fuse	No
Signalling at the device	Optic
Category type 2	Yes
Degree of protection (IP)	IP20
Product Standard/s	BS EN 61643-11
Terminal Capacity L&N	25 mm ²
Terminal Capacity E	25 mm ²
Frequency	50/60 Hz
requestion	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Product Specification Data (cont)	Revision Date: 15/10/2021
WEEE Symbol	Yes
UKCA Conformity	Yes

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

