

List No. NHTNSP250L NH DISTRIBUTION

250A 10kA Integral Surge Arrester Kit



- Accessory for NH Distribution Boards
- Supplied with Type 2 SPD, 10kA MCB (for SPD protection), cable loom kit & SPD mounting bracket
- 18th edition compliant
- Utilises bottom RH Way for protective MCB
- Nominal Voltage (AC) 240/415

System configuration TN System configuration TN-C System configuration TN-C-S System configuration TN-S System configuration TT Yes System configuration other No Number of conductors (without earthing) Nominal discharge surge current (8/20) Short-circuit breaking capacity (Isccr) Max. continuous voltage AC Max. discharge surge current (8/20) Max. discharge surge current (8/20) Max. discharge surge current (8/20) Mounting method Construction size Max. conductor cross section solid (solid, stranded) No No No No No No No No No N	
System configuration TN-C System configuration TN-C-S System configuration TN-S System configuration TT Yes System configuration TT Yes System configuration other No Number of conductors (without earthing) Alominal discharge surge current (8/20) Short-circuit breaking capacity (Isccr) Max. continuous voltage AC Max. discharge surge current (8/20) Mounting method DIN rail (Construction size Max. conductor cross section solid (solid, stranded) 35 mm²	
System configuration TN-C-S System configuration TN-S System configuration TT Yes System configuration other No Number of conductors (without earthing) Nominal discharge surge current (8/20) Short-circuit breaking capacity (Isccr) Max. continuous voltage AC Max. discharge surge current (8/20) Mounting method Construction size Max. conductor cross section solid (solid, stranded) Yes Yes Yes Yes Yes Yes Yes No	
System configuration TN-S System configuration TT Yes System configuration other No Number of conductors (without earthing) Aominal discharge surge current (8/20) Short-circuit breaking capacity (Isccr) 25 kA Max. continuous voltage AC Max. discharge surge current (8/20) 40 kA Mounting method DIN rail (Construction size 4 modula Max. conductor cross section solid (solid, stranded) 35 mm²	
System configuration TT System configuration other No Number of conductors (without earthing) Nominal discharge surge current (8/20) Short-circuit breaking capacity (Isccr) Max. continuous voltage AC Max. discharge surge current (8/20) Mounting method Construction size Max. conductor cross section solid (solid, stranded) Yes No	
System configuration other No Number of conductors (without earthing) Nominal discharge surge current (8/20) Short-circuit breaking capacity (Isccr) Max. continuous voltage AC Max. discharge surge current (8/20) Mounting method Construction size Max. conductor cross section solid (solid, stranded) No No A A A A A A A A A A A A A	
Number of conductors (without earthing) Nominal discharge surge current (8/20) Short-circuit breaking capacity (Isccr) Max. continuous voltage AC Max. discharge surge current (8/20) Mounting method Construction size Max. conductor cross section solid (solid, stranded) 4 4 4 4 4 4 4 4 4 4 4 4 4	
Nominal discharge surge current (8/20) Short-circuit breaking capacity (Isccr) Max. continuous voltage AC Max. discharge surge current (8/20) Mounting method Construction size Max. conductor cross section solid (solid, stranded) 20 kA 25 kA 350 V 40 kA DIN rail (** 4 modula 35 mm²	
Short-circuit breaking capacity (Isccr) 25 kA Max. continuous voltage AC Max. discharge surge current (8/20) Mounting method Construction size Max. conductor cross section solid (solid, stranded) 25 kA 25 kA 26 kA 27 Max. discharge surge current (8/20) 40 kA Mounting method A modula Max. conductor cross section solid (solid, stranded) 35 mm²	
Max. continuous voltage AC Max. discharge surge current (8/20) Mounting method DIN rail (** Construction size 4 modula* Max. conductor cross section solid (solid, stranded) 350 V 40 kA DIN rail (** 4 modula* 35 mm²	
Max. discharge surge current (8/20) Mounting method Construction size Max. conductor cross section solid (solid, stranded) 40 kA DIN rail (**) 4 modula 35 mm²	
Mounting method DIN rail (Construction size 4 modula Max. conductor cross section solid (solid, stranded) 35 mm ²	
Construction size 4 modula Max. conductor cross section solid (solid, stranded) 35 mm ²	
Max. conductor cross section solid (solid, stranded) 35 mm ²	top hat rail) 35 mm
, , , ,	r spacing
Max. conductor cross section flexible (fine-strand) 25 mm ²	
/oltage protection level L-N 1.4 kV	
/oltage protection level N-PE 1.5 kV	
Nith remote signalling contact Yes	
ntegrated backup fuse No	
Signalling at the device Optic	
Category type 2 Yes	
Degree of protection (IP)	
Product Standard/s BS EN 6	1643-11
Ferminal Capacity L&N 25 mm ²	
Ferminal Capacity E 25 mm ²	
Frequency 50/60 Hz	
CE Conformity Yes	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Product Specification Data (cont)	Revision Date: 01/12/2022
WEEE Symbol	Yes
UKCA Conformity	Yes

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

