



List No. NHVL3400MCCB

NH VM160

Incoming Device 400A 3P MCCB



- For NH VM160 Panel Boards
- Use in conjunction with inter-connection kit
- Electronic trip unit (LI) for system protection, with adjustable electronic elements
- Maximum cable lug connection/busbar 32mm wide
- Requires interconnection kit to connect to main busbars

Product Specification Data

Revision Date: 01/08/2022

Rated permanent current I _n	400 A
Rated voltage	690 V
Rated short-circuit breaking capacity I _{cu} at 400 V, 50 Hz	55 kA
Overload release current setting	160-400 A
Adjustment range undelayed short-circuit release	1.25-4400 A
Integrated earth fault protection	No
Type of electrical connection of main circuit	Other
Device construction	Complete device in housing
Suitable for DIN rail (top hat rail) mounting	No
DIN rail (top hat rail) mounting optional	No
Number of auxiliary contacts as normally closed contact	0
Number of auxiliary contacts as normally open contact	0
Number of auxiliary contacts as change-over contact	0
With switched-off indicator	No
With integrated under voltage release	No
Number of poles	3
Position of connection for main current circuit	Other
Type of control element	Toggle
Complete device with protection unit	Yes
Motor drive integrated	No
Motor drive optional	No
Degree of protection (IP)	IP20
Frequency	50/60 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Height	279 mm
Width	139 mm
Depth	163 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk