

List No. NHVSPCB324 NH VM160

32A 36kA 4P NHV MCCB ATFM c/w Box Terminals



- Adjustable Thermal & Fixed Magnetic Elements
- 36kA @ 415V AC to BS EN 60947-2
- Fitted with box terminals on line and load sides
- Maximum terminal capacity = 70mm²
- For use in NH VM160 outgoing Ways only

Product Specification Data	Revision Date: 19/02/2024	
Rated permanent current lu	32 A	
Rated voltage	500 V	
Rated short-circuit breaking capacity lcu at 400 V, 50 Hz	36 kA	
Overload release current setting	22-32 A	
Adjustment range undelayed short-circuit release	320-320 A	
Integrated earth fault protection	No	
Type of electrical connection of main circuit	Other	
Device construction	Complete device in housing	
Suitable for DIN rail (top hat rail) mounting	No	
DIN rail (top hat rail) mounting optional	No	
Number of auxiliary contacts as normally closed contact	0	
Number of auxiliary contacts as normally open contact	0	
Number of auxiliary contacts as change-over contact	0	
With switched-off indicator	No	
With integrated under voltage release	No	
Number of poles	4	
Position of connection for main current circuit	Other	
Type of control element	Toggle	
Complete device with protection unit	Yes	
Motor drive integrated	No	
Motor drive optional	No	
Degree of protection (IP)	IP40	
Product Standard/s	IEC 60947-2,-3,-4	
Frequency	50/60 Hz	
CE Conformity	Yes	
WEEE Symbol	Yes	
UKCA Conformity	Yes	
Height	130 mm	
Width	101 mm	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

roduct Specification Data (cont)	Revision Date. 19/02/2024
5	

Depth 70 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

