


List No. NM1406FLEX NH / NM / NMX 14 Way Consumer Unit Main Switch 100A, Flexible Configuration



- Includes a 100A main switch with twin line and neutral supply terminals and a 100A flexible busbar assembly
- Accepts all Wylex miniature final circuit protection devices; MCBs, RCBOs and AFDDs
- Accepts the Wylex miniature type 2 SPD, NMT2SPD3W/1
- Metal enclosure includes a full DIN rail with curved visor and temporary locking facility

Product Specification Data	Revision Date: 14/06/2022
Mounting method	Surface mounted (plaster)
Number of phases	1
Protection	Miniature- / earth leakage circuit breaker
Total number of groups	1
Number of poles main switch	2
Main switch rated current	100 A
Over voltage protection	No
Material housing	Steel
Degree of protection (IP)	IP2XC
Height	261 mm
Width	343 mm
Width in number of modular spacings	16
Depth	121 mm
Extension possible	No
With transparent cover	No
Lockable	Yes
Product Standard/s	BS EN 61439-3
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Amperage	100 A
Operating Voltage	230 V
Type of Current	AC
Consumer Unit Type	Main switch only
Total final circuit modular ways	14
Busbar type	Flexible
Main switch rating	100 A
Main switch final circuit modular ways	14

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Colour RAL

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE 01543 455000 www.electrium.co.uk info@electrium.co.uk