




## List No. NM9DSRCBMPVF

NH / NM / NMX

9W Consumer Unit with 100A Dual Supply Isolators, 16A DP Bi-Directional RCBO and PV MID Meter



- All metal PV consumer unit
- 9W Main switch only
- 40A Dual supply isolator and 16A 30mA DP Bi-Directional RCBO
- MID certified generation meter

Product Specification Data		Revision Date: 19/02/2024
Mounting method	Other	
Number of phases	1	
Protection	Miniature-/earth leakage circuit breaker	
Total number of groups	2	
Number of poles main switch	2	
Main switch rated current	100 A	
Over voltage protection	No	
Housing material	Steel	
Degree of protection (IP)	IP2XC	
Height	261 mm	
Width	343 mm	
Width in number of modular spacings	16	
Depth	121 mm	
Extension possible	No	
With transparent cover	No	
Lockable	Yes	
Product Standard/s	BS EN 61439-3	
Frequency	50 Hz	
CE Conformity	Yes	
WEEE Symbol	Yes	
UKCA Conformity	Yes	
Amperage	100 A	
Operating Voltage	230 V	
Type of Current	AC	
Consumer Unit Type	Main switch only	
Total final circuit modular ways	9	
Busbar type	Flexible	
Main switch rating	100 A	
Main switch final circuit modular ways	Flexible	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Bespoke application	Photovoltaic
Colour RAL	9010

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



**Electrium Sales Limited**, Walkmill Lane, Cannock WS11 0XE  
01543 455000 [www.electrium.co.uk](http://www.electrium.co.uk) [info@electrium.co.uk](mailto:info@electrium.co.uk)