

List No. NMIIX4506L

NH / NM / NMX

9 Way Dual Tariff Consumer Unit 100A Main Switch +4, 100A Main switch +5



- Fixed busbar assembly
- 4+5 Dual tariff
- 2x 100A main switch



Product Specification Data	Revision Date: 15/10/2021
Mounting method	Surface mounted (plaster)
Number of phases	1
Protection	Miniature- / earth leakage circuit breaker
Total number of groups	2
Number of poles main switch	2
Main switch rated current	100 A
Over voltage protection	No
Material housing	Steel
Degree of protection (IP)	IP2XC
Height	261 mm
Width	292 mm
Width in number of modular spacings	13
Depth	121 mm
Extension possible	No
With transparent cover	No
Lockable	Yes
Product Standard/s	BS EN 61439-3
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Amperage	100 A
Operating Voltage	230 V
Type of Current	AC
Consumer Unit Type	Dual tariff
Total final circuit modular ways	9
Busbar type	Fixed
Main switch rating	100 A
Main switch final circuit modular ways	4

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Product Specification Data (cont)	Revision Date: 15/10/2021
Colour RAL	9010
Main switch off peak tariff(s) rating	100 A
Main switch off peak tariff(s) modular ways	5

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

