



## List No. NMISS10SL100

NH / NM / NMX

10 Way Dual RCD Consumer Unit 100A Main Switch, 100A 30mA RCDs, Flexible Configuration



- Full metal enclosure
- Flexible busbar assembly
- 10W Dual RCD
- 2x 100A 30mA type A RCCBs

### Product Specification Data

Revision Date: 15/10/2021

Mounting method	Surface mounted (plaster)
Number of phases	1
Protection	Miniature- / earth leakage circuit breaker
Total number of groups	2
Number of poles main switch	2
Main switch rated current	100 A
Over voltage protection	No
Material housing	Steel
Degree of protection (IP)	IP2XC
Height	261 mm
Width	343 mm
Width in number of modular spacings	16
Depth	121 mm
Extension possible	No
With transparent cover	No
Lockable	Yes
Product Standard/s	BS EN 61439-3
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Amperage	100 A
Operating Voltage	230 V
Type of Current	AC
Consumer Unit Type	Dual RCD
Total final circuit modular ways	10
Busbar type	Flexible
Main switch rating	100 A
Main switch final circuit modular ways	0

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

RCD 1	100A 30mA type A
RCD 1 final circuit modular ways	Flexible
RCD 2	100A 30mA type A
RCD 2 final circuit modular ways	Flexible
Colour RAL	9010

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.