



List No. NMRCBO16BMPV NH / NM / NMX

PV Extension Consumer Unit 40A Main Switch, 16A DP
Bi-Directional RCBO and PV MID Meter



- All metal PV extension consumer unit
- 40A DP supply isolator
- 16A 30mA DP Bi-Directional RCBO
- MID certified generation meter

Product Specification Data

Revision Date: 19/02/2024

Mounting method	Other
Number of phases	1
Protection	Miniature-/earth leakage circuit breaker
Total number of groups	1
Number of poles main switch	2
Main switch rated current	40 A
Over voltage protection	No
Housing material	Steel
Degree of protection (IP)	IP2XC
Height	261 mm
Width	188 mm
Width in number of modular spacings	7
Depth	121 mm
Extension possible	No
With transparent cover	No
Lockable	Yes
Product Standard/s	BS EN 61439-3
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Operating Voltage	230 V
Type of Current	AC
Consumer Unit Type	PV Extension
Bespoke application	Photovoltaic
Colour RAL	9010

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.