



- Full metal enclosure
- Flexible busbar assembly
- 2W RCD incomer
- 63A 100mA type A RCCB

Product Specification Data	Revision Date: 15/10/202
Mounting method	Surface mounted (plaster)
Number of phases	1
Protection	Miniature- / earth leakage circuit breaker
Total number of groups	1
Over voltage protection	No
Material housing	Steel
Degree of protection (IP)	IP2XC
Height	185 mm
Width	130 mm
Width in number of modular spacings	4
Depth	104 mm
Extension possible	No
With transparent cover	No
Lockable	No
Product Standard/s	BS EN 61439-3
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Amperage	100 A
Operating Voltage	230 V
Type of Current	AC
Consumer Unit Type	RCD Incomer
Total final circuit modular ways	2
Busbar type	Flexible
RCD 1	63A 100mA type A
RCD 1 final circuit modular ways	2
Colour RAL	9010

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



**Electrium Sales Limited,** Walkmill Lane, Cannock WS11 0XE 01543 455000 www.electrium.co.uk info@electrium.co.uk