



## List No. NMRS10SLMDT

NH / NM / NMX

10 Way Split Load Dual Tariff Consumer Unit 100A Main Switch, 80A 30mA RCD and 100A MainSwitch, Flexible Configuration

# IMAGE NOT AVAILABLE

**For more information  
please contact the  
Technical Services  
Department**

- Full metal enclosure
- Flexible busbar assembly
- 10W Split load dual tariff
- 1x 100A main switch & 1x 80A 30mA RCCB
- 1x 100A Main switch

| Product Specification Data             |  | Revision Date: 25/01/2022 |
|--|--|---------------------------|
| Mounting method                        | Surface mounted (plaster)                  |                           |
| Number of phases                       | 1  |                           |
| Protection                             | Miniature- / earth leakage circuit breaker |                           |
| Total number of groups                 | 3  |                           |
| Number of poles main switch            | 2  |                           |
| Main switch rated current              | 100 A                                      |                           |
| Over voltage protection                | No   |                           |
| Material housing                       | Steel                                      |                           |
| Degree of protection (IP)              | IP2XC                                      |                           |
| Height                                 | 261 mm                                     |                           |
| Width                                  | 343 mm                                     |                           |
| Width in number of modular spacings    | 16   |                           |
| Depth                                  | 121 mm                                     |                           |
| Extension possible                     | No   |                           |
| With transparent cover                 | No   |                           |
| Lockable                               | Yes  |                           |
| Product Standard/s                     | BS EN 61439-3                              |                           |
| Frequency                              | 50 Hz                                      |                           |
| CE Conformity                          | Yes  |                           |
| WEEE Symbol                            | Yes  |                           |
| UKCA Conformity                        | Yes  |                           |
| Amperage                               | 100 A                                      |                           |
| Operating Voltage                      | 230 V                                      |                           |
| Type of Current                        | AC   |                           |
| Consumer Unit Type                     | Dual tariff                                |                           |
| Total final circuit modular ways       | 10   |                           |
| Busbar type                            | Flexible                                   |                           |
| Main switch rating                     | 100 A                                      |                           |
| Main switch final circuit modular ways | Flexible                                   |                           |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

|   |                 |
|---|-----------------|
| RCD 1                                       | 80A 30mA type A |
| RCD 1 final circuit modular ways            | Flexible        |
| Colour RAL                                  | 9010            |
| Main switch off peak tariff(s) rating       | 100 A           |
| Main switch off peak tariff(s) modular ways | Flexible        |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.