



List No. NMRS15SLMDT

NH / NM / NMX

15 Way Split Load Dual Tariff Consumer Unit 100A Main Switch, 80A 30mA RCD and 100A MainSwitch, Flexible Configuration



- Full metal enclosure
- Flexible busbar assembly
- 15W Split load dual tariff
- 1x 100A main switch & 1x 80A 30mA RCCB
- 1x 100A Main switch

Product Specification Data

Revision Date: 02/05/2024

Mounting method	Surface mounted
Number of phases	1
Protection	Miniature-/earth leakage circuit breaker
Total number of groups	3
Number of poles main switch	2
Main switch rated current	100 A
Over voltage protection	No
Housing material	Steel
Degree of protection (IP)	IP2XC
Height	261 mm
Width	438 mm
Width in number of modular spacings	21
Depth	121 mm
Extension possible	No
With transparent cover	No
Lockable	Yes
Product Standard/s	BS EN 61439-3
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Amperage	100 A
Operating Voltage	230 V
Type of Current	AC
Consumer Unit Type	Dual tariff
Total final circuit modular ways	15
Busbar type	Flexible
Main switch rating	100 A
Main switch final circuit modular ways	Flexible

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Product Specification Data (cont)		Revision Date: 02/05/2024
RCD 1	80A 30mA type A	
RCD 1 final circuit modular ways	Flexible	
Colour RAL	9010	
Main switch off peak tariff(s) rating	100 A	
Main switch off peak tariff(s) modular ways	Flexible	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk