



List No. NSPE-5580

NH / NM / NMX

Enclosed 40A 30mA DP Type B RCCB



- Enclosed double pole RCCB
- 40A 30mA Type B
- Enclosure 140x77x68mm
- Photovoltaic applications
- EV charging applications

Product Specification Data

Revision Date: 15/10/2021

Number of poles	2
Rated voltage	230 V
Rated current	40 A
Rated fault current	30 mA
Rated insulation voltage Ui	400 V
Mounting method	DIN rail
Leakage current type	B
Short-time delayed tripping	Yes
Frequency	50/60 Hz
Additional equipment possible	No
With interlocking device	No
Degree of protection (IP)	IP20
Width in number of modular spacings	4
Ambient temperature during operating	-25 - 45 °C
Connectable conductor cross section multi-wired	1.5 - 25 mm ²
Product Standard/s	IEC/EN 62423, IEC/EN 61543
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk