List No. REC2MSPD

Enclosed, Metal, 100A DP Supply Isolator with Type 2 SPD

- 100A Double pole switch disconnector
- Type 2 SPD
- 3 Part seal and secure metal enclosure
- Lockable switch handle

Product Specification Data	Revision Date: 11/12/2025
Version as main switch	No
Version as maintenance-/service switch	Yes
Max. rated operation voltage Ue AC	400 V
Rated operating voltage	230-400 V
Rated permanent current Iu	100 A
Conditioned rated short-circuit current Iq	16 kA
Number of poles	2
Motor drive optional	No
Voltage release optional	No
Suitable for distribution board installation	No
Type of control element	Toggle
Interlockable	No
Type of electrical connection of main circuit	Screw connection
Degree of protection (IP), front side	IP20
Product Standard/s	BS EN 60947-3, IEC EN 61643-11
Terminal Capacity L&N	50 mm²
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Height	220 mm
Width	88 mm
Depth	66 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Electrium Sales Limited, Walkmill Way, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk