List No. VX3030PSBK

FLAT PLATE DECORATIVE

10AX 1 Gang Intermediate Switch Polished Steel Finish

- Fully Rated for Fluorescent Loads
- Polished Steel Finish
- Black Interior
- 100W SBL LED Load

Product Specification Data	Revision Date: 11/10/2024
Product Standard/s	BS EN 60669-1
Terminal Capacity L&N	4 x 1.0, 3 x 1.5, 1 x 2.5 mm²
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Wiring system	Intermediate switch
Method of operation	Rocker/button
Assembly arrangement	Basic element
Number of modules (module system)	0
Push button switch	Yes
Number of rockers	1
Mounting method	Flush-mounted
Type of fastening	Screw mounting
With mounting plate	Yes
Material	Metal
Material quality	Stainless steel
Halogen free	Yes
Surface protection	Other
Surface finishing	Glossy
Colour	Chrome
Illumination	No
Function lighting	Other
Type of lighting	LED exchangeable
Suitable for degree of protection (IP)	IP2X
Nominal voltage	250 V
Rated current	10 A
Switching current for fluorescent lamps	10 AX
Connection type	Screwed terminal

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Device width	84.4 mm
Device height	84.4 mm
Min. depth of built-in installation box	16 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk