

List No. VX3252LVPS FLAT PLATE DECORATIVE

2 Gang 2 Way 250 Watt Mains/Low Voltage Dimmer Polished Steel Finish



- Push On/Off
- Polished Steel Finish

roduct Specification Data	Revision Date: 15/10/202
Product Standard/s	BS EN 60669-2-1
Terminal Capacity L&N	2 x 1.0, 1 x 2.5 mm ²
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Wiring system	Two-way switch
Method of operation	Turn button
Assembly arrangement	Basic element
Number of modules (module system)	0
Push button switch	Yes
Number of rockers	2
Mounting method	Flush mounted (plaster)
Type of fastening	Screw mounting
With mounting plate	Yes
Material	Metal
Material quality	Stainless steel
Halogen free	Yes
Surface protection	Other
Surface finishing	Glossy
Colour	Chrome
Illumination	No
Function lighting	Other
Type of lighting	Incandescent lamp
Suitable for degree of protection (IP)	IP2X
Nominal voltage	250 V
Rated current	1 A
Connection type	Screwed terminal
Width of device	84.4 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

Product Specification Data (cont)	Revision Date: 15/10/2021
Height of device	84.4 mm
Min. depth of built-in installation box	35 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

