

- Double Pole Switching
- Neon Indicator
- Safety Shutter System



Product Specification Data

Revision Date: 11/12/2025

Product Standard/s	BS 4177, BS 1363-2
Terminal Capacity L&N	2 x 6.0, 1 x 10, 1 x 16 mm ²
Terminal Capacity E	2 x 6.0, 1 x 10.0, 1 x 16.0 mm ²
Frequency	50 Hz
LRV Value	73
Printing	Off, On, Cooker, Socket
CE Conformity	Yes
WEEE Symbol	Yes
G Mark	Yes
UKCA Conformity	Yes
Wiring system	2-pole switch
Method of operation	Rocker/button
Assembly arrangement	Control element
Number of modules (module system)	0
Push button switch	Yes
Number of rockers	2
Mounting method	Flush-mounted
Type of fastening	Screw mounting
With mounting plate	Yes
Material	Plastic
Material quality	Other
Halogen free	Yes
Surface protection	Other
Surface finishing	Glossy
Colour	White
Illumination	Yes
Function lighting	Illuminated (on)
Suitable for degree of protection (IP)	IP2X
Nominal voltage	250 V

Rated current	45 A
Connection type	Screwed terminal
Device width	145 mm
Device height	85 mm
Min. depth of built-in installation box	47 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.