

List No. VX9985BK 1000 SERIES COMMUNICATION & DATA

USB Dual 2X1A 5V Output



- Push Fit Module
- Euro Module Solution

Terminal Capacity L&N 3 x 2.5 mm² LRV Value 4 Printing Charge CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes Assembly arrangement Modular device for domestic switching devices Utilization USB With dust cover No With iniged lid No Outlet direction Straight With imprint No Mounting method Module frame Material Plastic Material quality Thermoplastic Halogen free Yes Surface protection Other Surface finishing Glossy Colour Black Type of fastening Engage (snap) Number of modules (module system) 2 Suitable for number of connectors 2 Shielded housing No Width of device 50 mm Height of device 35.5 mm Min. depth of built-in installation box 35.5 mm	Product Specification Data	Revision Date: 15/10/2021
Printing Charge CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes Assembly arrangement Modular device for domestic switching devices Utilization USB With dust cover No With hinged lid No Outlet direction Straight With imprint No Mounting method Module frame Material Plastic Material quality Thermoplastic Halogen free Yes Surface protection Other Surface finishing Glossy Colour Black Type of fastening Engage (snap) Number of modules (module system) 2 Suitable for number of connectors 2 Shielded housing No Width of device 50 mm Beight of device 50 mm Depth of device 35.5 mm	Terminal Capacity L&N	3 x 2.5 mm ²
CE Conformity Yes WEEE Symbol Yes UKCA Conformity Yes Assembly arrangement Modular device for domestic switching devices Utilization USB With dust cover No With iniged lid No Outlet direction Straight With imprint No Mounting method Module frame Material Plastic Material quality Thermoplastic Halogen free Yes Surface protection Other Surface finishing Glossy Colour Black Type of fastening Engage (snap) Number of modules (module system) 2 Suitable for number of connectors 2 Shielded housing No Width of device 50 mm Height of device 50 mm	LRV Value	4
WEEE Symbol Yes UKCA Conformity Yes Assembly arrangement Modular device for domestic switching devices Utilization USB With dust cover No With hinged lid No Outlet direction Straight With imprint No Mounting method Module frame Material Plastic Material quality Thermoplastic Halogen free Yes Surface protection Other Surface finishing Glossy Colour Black Type of fastening Engage (snap) Number of modules (module system) 2 Suitable for number of connectors 2 Shielded housing No Width of device 50 mm Height of device 50 mm Depth of device 35.5 mm	Printing	Charge
UKCA Conformity Yes Assembly arrangement Modular device for domestic switching devices Utilization USB With dust cover No With hinged lid No Outlet direction Straight With imprint No Mounting method Module frame Material Plastic Material quality Thermoplastic Halogen free Yes Surface protection Other Surface finishing Glossy Colour Black Type of fastening Engage (snap) Number of modules (module system) 2 Suitable for number of connectors 2 Shielded housing No Width of device 50 mm Height of device 50 mm Depth of device 35.5 mm	CE Conformity	Yes
Assembly arrangementModular device for domestic switching devicesUtilizationUSBWith dust coverNoWith hinged lidNoOutlet directionStraightWith imprintNoMounting methodModule frameMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackType of fasteningEngage (snap)Number of modules (module system)2Suitable for number of connectors2Shielded housingNoWidth of device50 mmHeight of device50 mmDepth of device35.5 mm	WEEE Symbol	Yes
Utilization USB With dust cover No With hinged lid No Outlet direction Straight With imprint No Mounting method Module frame Material Plastic Material quality Thermoplastic Halogen free Yes Surface protection Other Surface finishing Glossy Colour Black Type of fastening Engage (snap) Number of modules (module system) 2 Suitable for number of connectors 2 Shielded housing No Width of device 50 mm Height of device 50 mm Depth of device 35.5 mm	UKCA Conformity	Yes
With dust cover No With hinged lid No Outlet direction Straight With imprint No Mounting method Module frame Material Plastic Material quality Thermoplastic Halogen free Yes Surface protection Other Surface finishing Glossy Colour Black Type of fastening Engage (snap) Number of modules (module system) 2 Suitable for number of connectors 2 Shielded housing No Width of device 50 mm Height of device 50 mm Depth of device 35.5 mm	Assembly arrangement	Modular device for domestic switching devices
With hinged lidNoOutlet directionStraightWith imprintNoMounting methodModule frameMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackType of fasteningEngage (snap)Number of modules (module system)2Suitable for number of connectors2Shielded housingNoWidth of device50 mmHeight of device50 mmDepth of device35.5 mm	Utilization	USB
Outlet directionStraightWith imprintNoMounting methodModule frameMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackType of fasteningEngage (snap)Number of modules (module system)2Suitable for number of connectors2Shielded housingNoWidth of device50 mmHeight of device50 mmDepth of device35.5 mm	With dust cover	No
With imprint Mounting method Module frame Material Material quality Material quality Halogen free Yes Surface protection Other Surface finishing Glossy Colour Black Type of fastening Engage (snap) Number of modules (module system) 2 Suitable for number of connectors 2 Shielded housing No Width of device Depth of device Depth of device Sudaule frame Module frame No Module frame Module frame Module frame No Module frame Module frame No Module frame Module frame No Module frame No Module frame Module frame No M	With hinged lid	No
Mounting methodModule frameMaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackType of fasteningEngage (snap)Number of modules (module system)2Suitable for number of connectors2Shielded housingNoWidth of device50 mmHeight of device50 mmDepth of device35.5 mm	Outlet direction	Straight
MaterialPlasticMaterial qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackType of fasteningEngage (snap)Number of modules (module system)2Suitable for number of connectors2Shielded housingNoWidth of device50 mmHeight of device50 mmDepth of device35.5 mm	With imprint	No
Material qualityThermoplasticHalogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackType of fasteningEngage (snap)Number of modules (module system)2Suitable for number of connectors2Shielded housingNoWidth of device50 mmHeight of device50 mmDepth of device35.5 mm	Mounting method	Module frame
Halogen freeYesSurface protectionOtherSurface finishingGlossyColourBlackType of fasteningEngage (snap)Number of modules (module system)2Suitable for number of connectors2Shielded housingNoWidth of device50 mmHeight of device50 mmDepth of device35.5 mm	Material	Plastic
Surface protectionOtherSurface finishingGlossyColourBlackType of fasteningEngage (snap)Number of modules (module system)2Suitable for number of connectors2Shielded housingNoWidth of device50 mmHeight of device50 mmDepth of device35.5 mm	Material quality	Thermoplastic
Surface finishing Colour Black Type of fastening Engage (snap) Number of modules (module system) 2 Suitable for number of connectors 2 Shielded housing No Width of device 50 mm Height of device 50 mm Depth of device 35.5 mm	Halogen free	Yes
ColourBlackType of fasteningEngage (snap)Number of modules (module system)2Suitable for number of connectors2Shielded housingNoWidth of device50 mmHeight of device50 mmDepth of device35.5 mm	Surface protection	Other
Type of fastening Number of modules (module system) Suitable for number of connectors Shielded housing No Width of device Depth of device Engage (snap) No Shielded housing No Shielded hou	Surface finishing	Glossy
Number of modules (module system)2Suitable for number of connectors2Shielded housingNoWidth of device50 mmHeight of device50 mmDepth of device35.5 mm	Colour	Black
Suitable for number of connectors Shielded housing No Width of device 50 mm Height of device 50 mm Depth of device 35.5 mm	Type of fastening	Engage (snap)
Shielded housing No Width of device 50 mm Height of device 50 mm Depth of device 35.5 mm	Number of modules (module system)	2
Width of device50 mmHeight of device50 mmDepth of device35.5 mm	Suitable for number of connectors	2
Height of device 50 mm Depth of device 35.5 mm	Shielded housing	No
Depth of device 35.5 mm	Width of device	50 mm
	Height of device	50 mm
Min. depth of built-in installation box 35 mm	Depth of device	35.5 mm
The soper of some in incomment box	Min. depth of built-in installation box	35 mm

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.

