



INSTALLATION INSTRUCTIONS

Padlockable door lock: PDDPL

Important

This unit should be installed by a qualified competent person in accordance with all relevant legislation and regulations including building regulations and wiring regulations BS7671. If in doubt contact a qualified competent person.

- **Turn off all power supplying this equipment before working on or inside the equipment.**
- Always use a properly rated volt-sensing device to confirm the power is off.
- Replace all devices, doors and covers before turning on the power to this equipment.
- To avoid ingress of swarf and similar material, always remove gland plates to allow cutting/slotting for cable entries to be effected remotely from the Distribution Board's Installation position.

Failure to follow these instructions could result in serious injury or death.

- 1) UNLOCK AND OPEN UNIT DOOR.
- 2) REMOVE KEY LOCK (UNSCREW HEX NUT ON INSIDE OF DOOR).
- 3) ASSEMBLE PADLOCK UNIT AS SHOWN AND INSERT INTO DOOR. FASTEN WITH HEX NUT FROM INSIDE OF DOOR AND TIGHTEN. SEE FIG 1.0.
- 4) ROTATE LOCK TO THE 'UNLOCKED' POSITION. DOOR CAN NOW BE CLOSED.
- 5) WITH THE DOOR CLOSED ROTATE LOCK TO THE 'LOCKED' POSITION AND ATTACH PADLOCK AS SHOWN IN FIG.1.1.

